According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

Paint for fabric.

Supplier: Plotteralia S.L.U. C/ Saturno, 13. Pol. Ind. La strella. 30500 Molina de Segura. Murcia. Tele-Nr. (+34)- 912 90 88 99

+34-91 562 04 20

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019



Flam. Lip. 2: H225 Highly flammable liquid and vapour.

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the U" in the latest valid version.

Warning! Pressurized container.

The classification is according to the latest editions of the U-lists, and extended by company and literature data.

The product is classified and labeled according to the CLP regulation.



GHS02

Danger

No Data Available

H225 Highly flammable liquid and vapour.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children..

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use..

P301 + P312 If swallowed: Call a poison center or doctor/physician if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Buildup of explosive mixtures possible without sufficient ventilation.

Not applicable. Not applicable.

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · Immediately wash with water and soap and rinse thoroughly.
- · Rinse opened eye for several minutes under running water.
- Drink plenty of water and provide fresh air. Call for a doctor immediately.
- No further relevant information available.

No further relevant information available.

Water spray(large fires only), foam, dry chemical or carbon dioxide.

- Water with full jet
- · No further relevant information available.
- . _
- · Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

 $Inform\ respective\ authorities\ in\ case\ of\ see page\ into\ water\ course\ or\ sewage\ system.$

Do not flush with water or aqueous cleansing agents
Dispose contaminated material as waste according to item 13.

nsure adequate ventilation.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

nsure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

No information.

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

•

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

.

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g.

KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Butyl rubber, BR

.

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

No date.

· Safety glasses

Appearance: Viscous liquid

Odour: Solvent

Odour threshold: 522ppm

pH: Not determined

Self-igniting Product is not self-igniting.

Melting point/freezing point: <-20°C

Boiling point: >46℃

Flash point: Not determined vaporation rate: 71%-78% Flammability (solid, gas): Flammable

Upper/lower flammability or explosive limits: Not determined

Vapour pressure: Not determined

Vapour density: Not determined Relative density: 0.707kg/m³ Vapour density Not determined

Solubility: Not water soluble. Re-dispersible in aromatic

. . . .

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

Stable under recommended storage and handling conditions.

No decomposition if used according to specifications.

No dangerous reactions known.

No further relevant information available.

No further relevant information available.

No dangerous decomposition products known.

No information.

- · Irritant to skin and mucous membranes.
- · No irritating effect.
- No sensitizing effects known.

The product shows the following dangers according to the calculation method of the General U Classification Guidelines for Preparations as issued in the latest version:

Harmful, Irritant, Vapours have narcotic effect.

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

No information.	
No information.	
No information.	
PBT:	
vPvB:	
Must not be disp	posed together with household garbage. Do not allow product to reach sewage system.
08 01 11* 15 01 04	waste paint and varnish containing organic solvents or other dangerous substances metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix
(for example asbestos), including empty pressure containers	
	Disposal must be made according to official regulations

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

UN1950

UN1950 PAINT

PAINT, flammable



Liquid.

3



3

3

Void

No

Warning: Liquid.

_

Not applicable.

According to (EU) No. 2015/830

Printing Date: 28.10.2019 Version Number 3 Revision date: 28/10/2019

·

Water hazard class 1 (Self-assessment): slightly hazardous for water.

A Chemical Safety Assessment has not been carried out.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H225 Highly flammable liquid and vapour.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children..

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use..

P301 + P312 If swallowed: Call a poison center or doctor/physician if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (uropean Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

IN CS: uropean Inventory of xisting Commercial Chemical Substances

LINCS: uropean List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, U)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2